

# XAE 950T

## automatic electronic condensate drain

- Suitable for use in compressed air systems
- Plug & Play
- Button test
- Competitive price-quality ratio
- High discharge capacity



Installation is recommended in compressed air systems to take away the condensate accumulated in pipes, reservoirs, filters and driers.

XAE 950-T has an embedded electronic circuit, a condensation sensor and an assisted-drive solenoid valve, which opens at pre-established intervals.

Valve opening time varies according to the actual quantity of condensation at the installation point.

This allows to limit compressed air waste to a minimum.

### Characteristics

Models	XAE-950T-230V	XAE-950-110V
Voltage	230 V- 50/60 Hz	115 V-50/60 Hz
Discharge flow rate	70 lt/h	
Control panel	2 LEDs indicate the power supply and the status of the discharger	
Push button test	1	
Operating pressure min. / max.	0,2— 16 bar	
Operating Temperature min. / max.	+ 1 °C / + 60 °C	
Weight	0,3 Kg	
Dimensions	Depth 100 mm / Height 120 mm / Width 62 mm	
Connections in	Fitting 1/4" Gas / M	
Connections out	Hose holder Ø 10 mm	
Electrical connection	EN 175301-803 Type A	
Protection degree	IP 65 ( with wired connector)	

Data contained in this bulletin are informative and subject to change without notice.

User is responsible for determining whether the product is fit for particular purpose and suitable for User's method of application.