


STERYFLON Plus ADM FREE



- Materials free from substances of animal origin (ADM FREE– Animal Derived Materials)
- Intrinsically Hydrophobic PTFE membrane
- High permeability versus gas
- Thermic cycles resistant
- Repeatedly steamable in situ or in autoclave
- Thermowelded construction
- Food contact materials according to EU and FDA requirements
- Bio-Safety per USP-Plastics
- Validation Guide available on request

STERYFLON Plus ADM FREE filter is "Animal Free" as the materials used for its manufacturing are free from animal derived substances. It is designed, manufactured and submitted to severe controls for applications in processes where the effluent is required to be free from particellar and biological contaminants.

The expanded PTFE membrane, intrinsically hydrophobic, allows superior performances both in gas filtration and non-aqueous liquid filtration. Bio-tech pharmaceutical, electronic, food & beverage industries can rely on a product with high standard of quality suitable to solve contamination issues on critical applications. Furthermore, the complete absence of animal derived substances makes it suitable for the newest and even more increasing market requirements.

STERYFLON Plus ADM FREE is manufactured within a controlled environment and each cartridge is integrity tested and is validated for bacterial retention correlated with microbiological challenge test. The retention is checked on regular sampling.

MATERIALS OF CONSTRUCTION

Filter media	PTFE membrane
Upstream supports	polypropylene
Downstream supports	polypropylene
Internal Core	polypropylene
External Cage	polypropylene
End caps / Adapters	polypropylene

FOOD-SAFETY

STERYFLON Plus ADM FREE filter element materials meet (EU) regulation 10/2011 and its amendments, regulations (EC) 1935/2004 and 1895/2005.

BIO-SAFETY

Filter media and components pass USP Biological Reactivity and Chemical-Physical tests for CLASS VI plastics. The filter meets USP "Water for injection" requirements for particle release and the effluent is Non-Pyrogenic per USP Bacterial Endotoxins (< 0,25 EU/ml).

QUALITY STANDARDS

Produced under a certified Quality System to guarantee traceability of manufacturing records and integrity testing results.

OPERATING CONDITIONS

- max. continuous temperature of fermentation inlet and exhaust air	70 °C
- max. continuous temperature for vent filter in recirculation loop	83 °C
- max. cumulative time of steam sterilization	150 hours at 140 °C with cycles of 30 minutes
- sanitization with chemicals	can be sanitized by standard chemical agents
- max. differential pressure	5,0 bar at 25 °C
- recommended change out differential pressure	2,0 bar at 25 °C

CODE	ABSOLUTE FILTRATION RATING		3) BACTERIAL RETENTION >10 ⁷ CFU/cm ²	ACCEPTABLE LIMIT FOR INTEGRITY TEST FOR 10" CARTRIDGE
	IN LIQUID	IN DRY GAS		
SJ	0,1 µm	< 0,01 µm	Acheleoplasma laidlawii in liquid	1) ≤ 25 ml/min @ 1,0 bar
SK	0,2 µm	< 0,01 µm	B. Diminuta in liquid / Batteriofago T1 in aerosol	1) ≤ 12 ml/min @ 0,8 bar
SKA	0,2 µm	< 0,01 µm	Brevundimonas diminuta in liquid	2) ≤ 16 Nml/10min @ 2,5 bar



Note:

1- The integrity is verified by DIFFUSION TEST using an aqueous solution of isopropyl alcohol (IPA 60/40 V/V) as wetting liquid.

2- The integrity is verified by WATER FLOW INTRUSION TEST.

3- Cartridges are validated for retention of the microorganism reported in the table according to ASTM F838.

AIR FLOW RATE FOR 10" CARTRIDGE



STERYFLON Plus ADM FREE ORDERING INFORMATION

PTFA - 207 1 - SJ - - PH

END FITTING	CODE
DOE: double open end with flat gaskets	200
SOE: open end with (2) O-Ring 2.222. Blind end with flat top.	203
SOE: open end with (2) O-Ring 2.226 and 2 bayonet locks. Blind end with fin.	207
SOE: open end with (2) O-Ring 2.222. Blind end with fin.	208
SOE: open end with (2) O-Ring 2.222 and 3 bayonet locks. Blind end with fin.	212

ABSOLUTE FILTRATION RATING micron	CODE
0,1	SJ *
0,2	SK *
0,2	SKA **

* Integrity by IPA diffusion test
** Integrity by water intrusion test

CODE	PRODUCT GRADE
PH	Non-pyrogenic Grade. Quality Certification in the box
PHH	Non-pyrogenic Grade. Quality Certification, with serial number, in the box

CODE	NOMINAL LENGTH
1	10"
2	20"
3	30"
4	40"

CODE	GASKETS	
No code	Standard	Silicone

Data contained in this bulletin are informative and subject to change without notice.
User is responsible for determining whether the product is fit for particular purpose and suitable for User's method of application.



Bea Technologies Spa Via Newton, 4 - 20016 Pero (Milano) ITALY
Tel +39 02 339271 FAX +39 02 3390713 e-mail: info@bea-italy.com
web: www.bea-italy.com