

# XAE-ADB-230V / XAE-ADB-115V

## Automatic electronic condensate drain

Automatic drain suitable for removing the condensate from pipeline, vessel, equipment and filters installed in compressed air systems.

The device opens the drain when the condensate is detected by the installed sensor; the drain remains open until all the liquid mixture has been removed; when the opening time exceeds 10 seconds, the cycle is extended to 60 seconds and reprogrammed.

Long period of condensate absence provides the progressive reduction of opening time to limit energy waste.



- Plug & Play
- Cost effective device
- High draining performances

### Characteristics

Models	XAE-ADB-230V	XAE-ADB-115V
Power supply	230 V – 50-60 Hz	115 V – 50/60 Hz
Maximum discharge power	210 l/h	
Control panel	2 LEDs: Power (Green) / Exhaust Discharger (Blue)	
Button test	1	
Operating pressure min. / max.	0,2 – 16 bar	
Operating Temperature min. / max.	+1 °C / +60 °C	
Weight	0,27 Kg	
Dimensions	103 x 98 x 62 mm	
Inlet connections	1 x G3/4" M with adapters G3/8" M – G1/4" M	
Outlet connections	Ø 10 mm	
Electrical connection	DIN 43650-A	
Assorbimento massimo	10 VA	
Protection degree	IP54	

The data are informative and subject to change without notice. User is responsible for determining whether the product is fit for particular purpose and suitable for User's method of application.

### Bea Technologies Spa

Via Newton,4 - 20016 Pero (MILANO) Italy

Tel.+(39) 02 339271 / Fax+(39) 02 3390713

mail:info@bea-italy.com

web:www.bea-italy.com